

MODELO	P6P03
DESCRIPCION	PATCHCORD UTP CAT6 SERIE PRO-II 90CM COLOR ROJO 41261R009


CATEGORY 6 PATCH CORD CABLE(P6P03)

General Features


- Available in 8 circuits (4 twisted pairs)
- Standard wires colours: Blue/Blue-white, Orange/Orange-white, Green/Green-white and Brown/Brown-white
- Available with/without shielding(UTP)
- Solid wire (AWG 24, 7/0.2BC)
- HDPE insulator
- PVC jacket
- Frequency: Maximun 250MHz
- Operating temperature: -20°C to +75°C
- Lengths: 0, 9m
- Connector Type: RJ45(8/8)
- Extreme termination 1: Modular plug
- Extreme termination 2: Modular plug
- Connection: 568B

Electrical Features

- DC-Loop resistance: $\leq 0.0658\Omega/m$
- Propagation speed: 0.64
- Propagation delay: 4.80-5.30 ns/m
- Delay skew < 100MHz < 0.20 ns/m
- Capacitance: f.f.s
- Return Loss (Min. at 250MHz): 15.60 dB
- Attenuation: (Min. at 250MHz): 39.40 dB
- Meet EIA/TIA 568 B.2, EN 50173-1, ISO/IEC 11801



PIN OUT



CN1(568B)		CN2(568B)
WHITE/ORANGE 1	↔	1 WHITE/ORANGE
ORANGE 2		2 ORANGE
WHITE/GREEN 3	↔	3 WHITE/GREEN
GREEN 6		6 GREEN
BLUE 4	↔	4 BLUE
WHITE/BLUE 5		5 WHITE/BLUE
WHITE/BROWN 7	↔	7 WHITE/BROWN
BROWN 8		8 BROWN