



Part Number: 5504UE

Security & Sound, #22-6c, BC, CMR

Product Description

Security & Sound Cable, Riser-CMR, 6-22 AWG stranded bare copper conductors with polyolefin insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

| | | Suitable Applications: | Security Systems, Intercom/PA Systems, Sound/Audio Systems, Power Limited Controls, and Single Line Telephone. |
|--|--|------------------------|--|
|--|--|------------------------|--|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|--------------------|-------------|------------------|-------------------|
| 22 | 7x30 | BC - Bare Copper | 6 |
| Condu | ctor Count: | | 6 |
| Conductor Size: 22 | | 22 AWG | |

Insulation

| Material | Nominal Wall Thickness |
|--------------------|------------------------|
| PP - Polypropylene | 0.008 in |

Color Chart

| Number | Color | Number | Color |
|--------|-------|--------|-------|
| 1 | Black | 4 | Green |
| 2 | Red | 5 | Brown |
| 3 | White | 6 | Blue |

Outer Shield Material



Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.168 in | 0.017 in | Yes |

Construction and Dimensions

Cabling

| Lay Direction | Twists |
|---------------|--------------|
| Left Hand | 4.8 twist/ft |

Electrical Characteristics

Conductor DCR



Capacitance

Nom. Capacitance Conductor to Conductor 17 pF/ft

Current

| Element | Max. Recommended Current [A] |
|----------------------|-------------------------------|
| 10C Temperature Rise | 2 Amps per conductor @ 25°C A |

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

| UL Temp Rating: | 75°C |
|-----------------------|----------------|
| Operating Temp Range: | -20°C To +75°C |

Mechanical Characteristics

| Bulk Cable Weight: | 19 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 54.6 lbs |
| Min Bend Radius/Minor Axis: | 1.625 in |

Standards

| NEC Articles: | 800 |
|--------------------------|-----|
| CEC/C(UL) Specification: | CMG |
| CPR Euroclass: | Eca |

Applicable Environmental and Other Programs

| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
|---------------------------------------|-------------------------------|
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Indoor: Yes |
|---------------------------|
|---------------------------|

Flammability, LS0H, Toxicity Testing

| C(UL) Flammability: | FT4 |
|-----------------------|---------------|
| UL Flammability: | UL1666 Riser |
| ISO/IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| Plenum (Y/N): | No |
|----------------|--------|
| Plenum Number: | 6504UE |

Part Number

Variants

| Item # | Color | UPC | Length | Footnote |
|-----------------|--------|--------------|---------|----------|
| 5504UE.001000 | Chrome | | 1,000 m | |
| 5504UE.00305 | Chrome | | 305 m | |
| 5504UE 0081000 | Gray | 612825163800 | | С |
| 5504UE 008500 | Gray | 612825163817 | | |
| 5504UE 008C500 | Gray | | | |
| 5504UE 008U1000 | Gray | 612825163794 | | |
| 5504UE 009C500 | White | 612825163824 | | |
| 5504UE 009U1000 | White | 612825163831 | | |
| 5504UE 009U500 | White | 612825163848 | | |

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision:

Revision Number: 0.203 Revision Date: 12-19-2018

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.