



**Part Number: 8241**

Analog Video, RG59, 23 AWG Solid BCCS, 95% BC Braid, PVC Jacket, CM

**Product Description**

23 AWG Solid .023" bare copper-covered steel conductor, polyethylene insulation, bare copper braid shield (95% coverage), PVC jacket.

**Technical Specifications**

**Product Overview**

Environmental Space:	Outdoor - Aerial
----------------------	------------------

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Nominal Diameter	No. of Coax
23	Solid	BCCS - Bare Copper Covered Steel	0.023 in	1

Conductor Count:	1
------------------	---

**Insulation**

Material	Nominal Diameter
PE - Polyethylene	0.146 in

**Outer Shield Material**

Type	Material	Coverage [%]
Braid	BC - Bare Copper	95 %

**Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.24 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
49 Ohm/1000ft	2.6 Ohm/1000ft	2.6 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Shield
20.5 pF/ft

**Inductance**

Nominal Inductance
0.131 µH/ft

**Impedance**

Nominal Characteristic Impedance
75 Ohm

**High Frequency (Nominal/Typical)**

Frequency [MHz]	Nom. Insertion Loss
-----------------	---------------------

1 MHz	0.6 dB/100ft
10 MHz	1.1 dB/100ft
50 MHz	2.4 dB/100ft
100 MHz	3.4 dB/100ft
200 MHz	4.9 dB/100ft
400 MHz	7 dB/100ft
700 MHz	9.7 dB/100ft
900 MHz	11.1 dB/100ft
1000 MHz	12 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.54 ns/ft	66 %

#### Power Rating

Frequency [MHz]	Max. Power Rating [W]	Nominal Power Rating [W]
50 MHz	470 W	470 W
100 MHz	310 W	310 W
300 MHz	160 W	160 W
500 MHz	115 W	115 W
1,000 MHz	76 W	76 W

#### Voltage

Non-UL Voltage Rating	UL Voltage Rating
1700 V RMS	30 V RMS (AWM 1354), 300 V RMS (CM)
	30 V RMS

#### Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-40°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight:	37 lbs/1000ft
Max Recommended Pulling Tension:	62 lbs
Min Bend Radius/Minor Axis:	2.5 in

#### Standards

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
UL AWM Style:	UL Style 1354
CPR Euroclass:	Eca
RG Type:	59/U Type

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Aerial:	Yes - Black only, when supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	30 V RMS (UL AWM Style 1354), 300 V RMS (UL CM)

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	88241, 82241

## Part Number

### Variants

Item #	Color	UPC	Length	Footnote
8241 010100	Black	612825358695	100 ft	
8241 0101000	Black	612825356011	1,000 ft	C
8241 0102000	Black	612825358701	2,000 ft	C
8241 010500	Black	612825355717	500 ft	C
8241 0105000	Black	612825358640	5,000 ft	C
8241 010U1000	Black	612825358060	1,000 ft	
8241 010U500	Black	612825355977	500 ft	
8241 006U1000	Blue, Light	612825357629	1,000 ft	
8241 005U1000	Green, Dark	612825358039	1,000 ft	
8241 003U1000	Orange	612825355601	1,000 ft	
8241 002U1000	Red	612825358046	1,000 ft	
8241 009U1000	White	612825358688	1,000 ft	
8241 004U1000	Yellow	612825355595	1,000 ft	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

## History

Update and Revision:	Revision Number: 0.259 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.