



Product: [FXU Blank Frame](#)

FX Ultra Blank Frame

Product Description

FX Ultra Blank Plate

Technical Specifications

Part Number:	FFZH00BB
--------------	----------

Product Overview

Environmental Space:	Indoor
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers

Construction

Weight:	4.46 kg
Height:	1.5 m
Depth:	2.2

Temperature Range

Operating Temp Range:	-10 to 60°C
Storage Temp Range:	-10 to 75°C

Product Material

Materials

Description	Material	Color
Frame	Plastic - UL94V-0	Black

Standards

EU RoHS Compliance Date (yyyy-mm-dd):	2006-01-07
MII Order #39 (China RoHS):	EUP 50

Additional Notes

Packaging:	Individually packaged in a plastic shell, Shipped in cardboard box (60/box)
Related Parts:	FiberExpress Ultra Patch panels, Pre-terminated MPO low loss cable assemblies

History

Variants

Item #	Color	Connector Type	Port Count
FFZH00BB	Black	Blank	0 Port

Update and Revision:	Revision Number: 0.52 Revision Date: 01-31-2020
----------------------	---

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.