

5663U6 Multi-Conductor - Compliant Cat 6 for Video, Sound and Security Applications



For more Information
please call

1-800-Belden1



General Description:

Surveillance Category Cable, Riser-CMR, Cat6 (250 MHz), 4-23 AWG Solid Bare Copper Pairs with polyolefin insulation, UTP, PVC jacket with ripcord

Usage (Overall)

Suitable Applications: Video, Sound & Security, Premise Horizontal Cable, Gigabit Ethernet, 100GazeTX, 100BaseVG ANYLAN, 155 ATM, 622 ATM, 250MHz CAT6

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors: 8

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
5.588

Outer Jacket Ripcord: Yes

Overall Cable

Overall Nominal Diameter: 5.588 mm

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe and Blue
2	White/Orange Stripe and Orange
3	White/Green Stripe and Green
4	White/Brown Stripe and Brown

Mechanical Characteristics (Overall)

Storage Temperature Range: -20°C To +60°C

Installation Temperature Range: 0°C To +60°C

5663U6 Multi-Conductor - Compliant Cat 6 for Video, Sound and Security Applications

Operating Temperature Range:	-20°C To +60°C
Bulk Cable Weight:	34.229 Kg/Km
Max. Recommended Pulling Tension:	177.928 N
Min. Bend Radius/Minor Axis:	22.860 mm
Min. Bend/Installation:	56.134 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	03/19/2009
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2
Other Specification:	Third party Verified to Category 6

Applicable Patents:

Country
www.belden.com/p

Flame Test

UL Flame Test:	UL1666 Vertical Riser
C(UL) Flame Test:	FT4
CSA Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Aerial:	No
Suitability - Burial:	No
Sunlight Resistance:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6663U6

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/m)
49.215

Maximum Capacitance Unbalance (pF/100 m):	330
---	-----

Nominal Velocity of Propagation:

VP (%)
70

METRIC MEASUREMENT VERSION

5663U6 Multi-Conductor - Compliant Cat 6 for Video, Sound and Security Applications

Maximum Delay:

Delay (ns/100 m)
537 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
45

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
9.380

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
5

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
1	2.000	74.3	72.3	72.3	70.3	20.000	na
4	3.800	65.3	63.3	61.5	59.5	23.000	na
8	5.300	60.8	58.8	55.4	53.4	24.500	na
10	6.000	59.3	57.3	53.3	51.3	25.000	na
16	7.600	56.2	54.3	48.7	46.7	25.000	na
20	8.500	54.8	52.8	46.3	44.3	25.000	na
25	9.500	53.3	51.3	43.8	41.8	24.300	na
31.25	10.700	51.9	49.9	41.2	39.2	23.600	na
62.5	15.400	47.4	45.4	32.0	30.0	21.500	na
100	19.800	44.3	42.3	24.5	22.5	20.100	na
155	25.200	41.5	39.5	16.3	14.3	18.800	na
200	29.000	39.8	37.8	10.8	8.8	18.000	na
250	32.800	38.3	36.3	5.5	3.5	17.300	na

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	67.8	64.8
4	100 ± 15	100 ± 15	55.8	52.7
8	100 ± 15	100 ± 15	49.7	46.7
10	100 ± 15	100 ± 15	47.8	44.8
16	100 ± 15	100 ± 15	43.7	40.7
20	100 ± 15	100 ± 15	41.8	38.8
25	100 ± 15	100 ± 15	39.8	36.8
31.25	100 ± 15	100 ± 15	37.9	34.9
62.5	100 ± 15	100 ± 15	31.9	28.9
100	100 ± 15	100 ± 15	27.8	24.8
155	100 ± 20	100 ± 15	23.9	20.9
200	100 ± 20	100 ± 15	21.8	18.8
250	100 ± 20	100 ± 15	19.8	16.8

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft. intervals. Third party verified to ANSI/TIA-568-C.2, Category 6.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5663U6 0091000	1,000 FT	24.000 LB	WHITE		4 PR #24 PO FRPVC
5663U6 0101000	1,000 FT	24.000 LB	BLACK	C	4 PR #24 PO FRPVC
5663U6 0105000	500 FT	12.500 LB	BLACK		4 PR #24 PO FRPVC

METRIC MEASUREMENT VERSION

5663U6 Multi-Conductor - Compliant Cat 6 for Video, Sound and Security Applications

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 8 Revision Date: 09-18-2017

© 2020 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).